

LANOTEC® Product Data Sheet Anti-Spatter (AS)

Derived from natural, sustainable ingredients

Welding Anti-Spatter



Always read entire label before using product

- FEATURES:**
- Non Flammable
 - Does not affect galvanising process
 - Ideal for confined spaces
 - No Methylene Chloride
 - Versatile & Safe

CONTENTS: Lanolin (a natural product), blended with an evaporative carrier to enable ease of application and enhance penetration

USAGE EXAMPLES:

- Welding anti-spatter for mig and arc welding
- Lubricant for cutting, tapping, drilling and pressing
- Corrosion and spatter protection of welding beds, robots and spot welders
- Can be used to protect and prolong the life of welding gloves and aprons
- Welding nozzle protection

STORAGE & TRANSPORT:

- Aerosols classified as Dangerous Goods for transport and storage (UN 1950; DG 2.1 2YE)
- All other sizes are not classified as DG
- Keep in cool, dry, well ventilated place
- Keep out of reach of children
- Shelf life - virtually indefinite if kept sealed in reasonable conditions



PREPARATION:

- Best applied to dry, clean surfaces
- Anti-Spatter (AS) can be sprayed to corrosive surfaces to stop further corrosion

APPLICATION:

- Shake container to ensure product is mixed correctly. Colder climates will require extra agitation.
- Lanotec Anti-Spatter can be applied via spray

REMOVAL:

- Lanotec recommends the use of Lanotec Citra-Force™ or Lanotec PowaWash™.

TESTING:

- Test welds meet Standard AS/NZS 1554.1 2004 Category SP

NATURAL • ENVIRONMENTAL • SUSTAINABLE

SUPPLIED BY



**TRIMAR
EUROLUBE**

FOR MORE INFORMATION: Lanotec Australia Pty Ltd
PO Box 360 Archerfield QLD 4108 07 3373 3700 info@lanotec.com.au

For safe handling of this product, please consult the Safety Data Sheet (SDS)

www.lanotec.com.au

Controlled Document - LAN-0011 PDS-AS | Version 5.0 June 2021

