



# DATA SHEET

DS-T41-R3 231123



## T41 Seawater antifouulant



Product name	T41 Seawater antifouulant
Product type	Anti foulant
PN	T41
Packaging:	25 l pail
Characteristics	Liquid

**Trimar Eurolube (Thailand) Co., Ltd.**

**108/10 Moo 6 Najomtien Sattahip**

**20250 Chonburi Thailand**

**[www.eurolube.net](http://www.eurolube.net) [sales@eurolube.net](mailto:sales@eurolube.net)**

**One Stop Shop**

**Oilfield and Industrial consumables and materials**

### What?

T41 seawater antifoulant is used to prevent marine growth and seawater fouling in flowing or static conditions. Prevents build up of mussels, barnacles, algae, tube-worms and other aquatic foulants.

### Where?

Use in any seawater system such as cooling, fire-water, trim and ballast etc.



### How?

For flowing conditions:

By chemical dosing pump inject T41 at inlet point such as seastrainer. Inject 6ppm for one hour each 24 hour period in coastal waters. Initiate and maintain this treatment 3 day before and after entering and leaving coastal waters.

For static conditions (Tanks):

Add 100 ppm T41 to the tanks at loading. After that add 20ppm each month.



### Why?

- Protect piping and tanks from marine fouling
- Corrosion protection
- Increase system efficiency
- Reduce maintenance requirements