

Derived from natural, sustainable ingredients

Lubricant | Corrosion Inhibitor



<u>Code</u>	<u>Sizes</u>
HWRL05	5 Litre
HWRL20-CUBE	20 Litre

FEATURES:

- High resistance to acids & salts
- Resists wash off
- Provides long lasting lubrication & corrosion protection
- Penetrates to the core of the rope
- Compatible with most coating systems
- Contains no Silicones

CONTENTS:

Lanolin (a natural product), blended with an evaporative carrier to enable ease of application & enhance penetration

APPLICATIONS:

- Suitable for all wire ropes above 16mm or any wire ropes operating in corrosive environments
- Ideal for rig & marine cranes, or any wire ropes working in the splash zone
- Ideal for use around waterways & coastal environments
- Lubrication of ropes in environmentally sensitive areas where salt water is an issue
- Ideal for use on industrial high load bearing chains

PREPARATION:

- Inspect wire rope for damage.
- Clean wire rope if practical for best results using wire brush or high pressure water to remove foreign debris.
- (WRL) is compatible with all oil based manufacturers lubricants.
- For wash-off resistant & full effectiveness, allow approximately one hour for evaporation of solvent.

RE-APPLICATION:

- With wire ropes over 16mm a quarterly visual inspection is recommended. (WRL) should be reapplied at this time.
- Since (WRL) is a long lasting high performance product, it can be reapplied during your normal wire rope lubrication service intervals.

CLEANING:

- Use a biodegradable degreaser or solvent such as Lanotec Citra-Force™ or PowaWash™.

STORAGE & TRANSPORT:

- Bulk liquid is non-DG
- Keep in cool, dry, well ventilated place
- Keep out of reach of children
- Shelf life - virtually indefinite if kept sealed in reasonable conditions
- Stirred container to ensure product is mixed correctly. Colder climates will require extra agitation.
- (WRL) is spray-able when above 25°C, or can also be hand applied or brushed on at any temperature.
- Place catching container under lube zone to collect any spills or overflow.
- Apply enough (WRL) to fill the valley of the wire rope only.
- Can be sprayed or dipped.